

CMMR4K120-V | DATASHEET

45° first surface mirror for 144.0 x 38.5 mm clamping diameter optics, right angle vertical bend



KEY ADVANTAGES

Reflect light at 90°.

Ideal for **limited space**.

Easy and secure clamping system.

Compatible with telecentric lenses and illuminators.

Optional **protective windows** available.



SPECIFICATIONS

Optical specifications

Coating	Aluminium reflective coating, R>90%, bandwidth 430-670 nm	
Deviation angle	(°)	90
Protective windows	No	


Mechanical specifications

Clamping size	(mm)	144.0 x 38.5
Clamping system	mounting screws	
Working distance difference ¹	(mm)	43.3
Length	(mm)	199.3
Width	(mm)	177.0
Height	(mm)	72.0
Mass	(g)	659

¹ Value to be subtracted from the objective or illuminator working distance when the CMBS is used

CMMR SETUP

CMMR4K-V bends the light rays vertically. UPWARD BEND



COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.